

BLUEFISH XH flexible hose

NS9416:2013 approved for landbased fish farming.



Specially designed transparent hose for maritime applications, including onshore and offshore aquaculture. Also suitable for the suction and transport of abrasive particles, granules, waste, plastics, wood materials, and agricultural products. Ideal for use in high-humidity environments.

Features a polyether-polyurethane wall reinforced with a rigid, impact-resistant PVC helix. Offers excellent resistance to hydrolysis, microbes, oils, chemicals, abrasion, and wear. The PRO coating on the PVC spiral ensures smooth and easy gliding across surfaces.

Working temperature: -40°C to +80°C.

Product no.	Int. diameter (mm)	Ext. diameter (mm)	Working pressure (bar)	Vacuum (m H2O)	Bending radius (mm)	Weight (kg/m)	Length (m)
22-7270-63	63	na	1,4	7,0	69	0,63	25
22-7270-76	76	na	1,4	6,5	80	0,77	30
22-7271-02	102	na	1,2	6,0	110	1,17	20/30
22-7271-10	110	na	1,1	5,5	118	1,35	20/30
22-7271-27	127	na	1,0	5,0	135	1,56	20/30
22-7271-52	152	na	0,8	5,0	150	2,36	20
22-7271-60	160	na	0,8	4,5	170	2,57	20
22-7272-03	203	na	0,5	4,0	250	3,26	12

Technical data @ 20° C